



Amigo 7X

Android TV operator tier certified UHD client TV device



Features

- Android TV Operator Tier certified
- 4Kp75,10-bit UHD resolution
- 802.11ac dual band 2x2 WiFi
- High Dynamic Range (HDR) processing including HDR10 and HLG
- Video and audio codec support including HEVC, MPEG-4 AVC (H.264), Dolby Digital Plus and VP9
- MicroSD card slot for additional storage and Pause Live TV
- IR and Bluetooth connectivity
- Hybrid Tuner Options
- Content protection via Widevine, Playready or Verimatrix Ultra
- Self-install wizard to simplify deployment

Overview

- Deliver a modern user experience with an operator branded Android TV User Interface providing consumers with access to linear channels and streaming apps
- Powered by AminoOS software simplifying integration with a wide variety of middleware and DRM solutions, as well as existing infrastructure such as multicast, MPEG 2, retransmission and more.
- Sleek compact design combined with IR or Bluetooth connectivity enables out-of-sight positioning in the home
- Backed by Amino expertise in managing the Android TV certification process

All Amino Devices are enhanced with Amino Engage, our SaaS platform streamlining device deployment and management, including app updates, while enhancing customer support.



Specifications

| Processing | |
|---|---|
| CPU | 18.5K DMIPS |
| DRAM | 2GB |
| Flash | 8GB eMMC (Options for 16GB) |
| Software | |
| Operating System | Android TV Operator Tier certified |
| Audio / Video Interfaces | |
| Digital Video | HDMI 2.1 |
| Analog Video | CVBS + L/R Audio |
| Video Formats | |
| Video Resolutions | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p60, 2160p60 10-bit |
| Audio Codecs | Dolby Digital, Dolby Digital Plus, MPEG I Layer 1 and 2, LC-ACC & HE-AAC |
| Video Codecs | AVC/H.264 High Profile @ Level 4.2, HEVC/H.265, MPEG-1/H.261/H.263, MPEG-2 Main Profile @ High Level, VP9 |
| Other codecs on request | |
| Tuner | |
| Optional DVB-C/T/T2 software switchable | |
| Other Interfaces | |
| Ethernet | 10/100 Base-T |
| Wi-Fi | 2x2 802.11ac/n dual-band selectable |
| Remote Control Support | IR 36kHz / BLE |
| USB | 1 x USB 3.0, 1 USB x 2.0 |
| Status LED | Power/Standby, IR Activity, Network Activity |
| SD Card Slot | IP version only |
| Regulatory Compliance | |
| Environment and Safety | FCC Certified, CB Certified, CE Certified and RoHS Compliant |
| Power | |
| Power Supply | External, 12V/1A |
| Power Consumption | 10.5W maximum, fully equipped |
| Operating Environment | |
| Temperature | -5°C to 40°C (23°F to 104°F) |
| Humidity | 5-85% (non-condensing) |
| Physical Properties | |
| Size (L*W*H) | 120 mm x 120 mm x 28 mm |
| Weight | 230g |

Customer Support

To find out more please contact an Amino representative:

sales@amino.tv

amino.tv

